

Large Capacity Manual & Motor Hose Reels

1185 & 1195 Series

1185 and 1195 Series hand crank and motor driven hose reels are designed to handle long lengths of large diameter hose for increased volume delivery. The exclusive low profile outlet riser and open drum design provide a non-crimping, flat smooth hose wrap. The sturdy all welded "A" frame base provides exceptional strength to handle the extra weight without sacrificing performance, even in demanding mobile applications.

1185 SERIES Offers...

- Swivel Is Bolted Directly To The Bearing Housing
- Low Profile Outlet Riser & Open Hose Slot For Even Hose Wraps
- Horizontal Surface Mount Bearings Instead Of Flange Mounted
- Brake Assembly Provides Adj. Friction To Brake Or Lock The Drum
- One Piece All Welded Steel "A" Frame Construction



MOTOR

MANUAL

SPRING

Drive Type

Manual

Motor

Media

Air,

Water

Oil

Grease

Fuel

Swivel material

Steel

Seal material

Nitrile

1185 HAND CRANK MODELS // Air & Water & Oil

MODEL no hose	I.D.	O.D.	Length	I.D.*	O.D.*	Length*	BAR	Inlet FNPT	Outlet FNPT	KG	Size
1185-1124	38 mm	51 mm	15 m	32 mm	44 mm	23 m	41	1.5"	1.5"	35	1
1185-1524	38 mm	51 mm	23 m	32 mm	44 mm	30 m	41	1.5"	1.5"	37	2
1185-2020	38 mm	51 mm	21 m	32 mm	44 mm	24 m	41	1.5"	1.5"	32	3
1185-2024	38 mm	51 mm	30 m	32 mm	44 mm	38 m	41	1.5"	1.5"	43	4
1185-2028	38 mm	51 mm	38 m	32 mm	44 mm	55 m	41	1.5"	1.5"	49	5
1185-2528	38 mm	51 mm	46 m	32 mm	44 mm	67 m	41	1.5"	1.5"	55	6
1185-3324	38 mm	51 mm	53 m	32 mm	44 mm	68 m	41	1.5"	1.5"	70	7
1185-3328	38 mm	51 mm	76 m	32 mm	44 mm	99 m	41	1.5"	1.5"	77	8

* Adapter required

1195-BXXX-XP HAND CRANK MODELS // Air & Water & Oil

MODEL no hose	I.D.	O.D.	Length	I.D.*	O.D.*	Length*	BAR	Inlet FBSP	Outlet MBSP	KG	Size
1195-932-BXXX-XP	51 mm	65 mm	15 m	38 mm	57 mm	18 m	41	2"	2"	58	9
1195-1332-BXXX-XP	51 mm	65 mm	23 m	38 mm	57 mm	30 m	41	2"	2"	67	10
1195-2032-BXXX-XP	51 mm	65 mm	35 m	38 mm	57 mm	45 m	41	2"	2"	84	11
1195-1728-BXXX-XP	51 mm	65 mm	18 m	38 mm	57 mm	26 m	41	2"	2"	61	12
1195-2428-BXXX-XP	51 mm	65 mm	27 m	38 mm	57 mm	41 m	41	2"	2"	77	13
1195-3228-BXXX-XP	51 mm	65 mm	38 m	38 mm	57 mm	53 m	41	2"	2"	99	14

MOTORS DRIVEN MODELS // Add the suffix to hand crank models above


* Adapter required

Suffix #	Motor Type	Description	Extra KG
E	ELECTRIC - 12V DC	1/3 HP	6
EF	ELECTRIC - 24V DC	1/3 HP	6
ED	ELECTRIC - 12V DC XP	1/2 HP	12
EB	ELECTRIC - 24V DC XP	1/2 HP	12
EA	ELECTRIC - 115V DC XP	1/2 HP	12
EJ	ELECTRIC - 230V XP	1/2 HP	12
A	AIR REWIND	4AM	4
AB	AIR REWIND	6AM	6
H	HYDRAULIC REWIND	END PORTED 9/16-18 UNF	3
C	CRANK	BEVEL CRANK	0


DIMENSIONS (in mm)

SIZE	A	B	C	D	Crank E	Elec E	Air E	F	G
1	267	292	610	432	635	664	594	564	635
2	267	394	610	535	737	766	696	564	635
3	267	292	508	650	851	880	810	498	549
4	267	508	610	636	851	880	810	564	635
5	267	508	711	636	851	880	810	622	737
6	267	635	711	764	978	1007	937	568	737
7	267	838	610	967	1182	1210	1140	622	635
8	267	838	711	967	1182	1210	1140	622	737
9	394	241	813	385	454	562	493	650	845
10	394	343	813	485	658	766	696	650	845
11	394	508	813	650	556	664	594	650	845
12	394	445	711	587	823	931	861	622	768
13	394	610	711	752	721	829	759	622	768
14	394	813	711	955	1026	1134	1064	622	768

1185 SERIES CRANK



1185 SERIES MOTOR



1195 SERIES MOTOR

